

Cotto Americana

PORCELAIN STONE

• Cotto Americana by Crossville offers the timeless appeal of traditional styling updated with contemporary colors.

• With a variety of sizes, including mosaics, it's the perfect combination for today's American design landscape



AV171 Beige



12" x 12"



18" x 18"



2" x 2" Mosaic



6" x 6"



AV172 Tan



12" x 12"



18" x 18"



2" x 2" Mosaic



6" x 6"



AV173 Red



12" x 12"



18" x 18"



2" x 2" Mosaic



6" x 6"



AV174 Brown



12" x 12"



18" x 18"



2" x 2" Mosaic



6" x 6"




AV175 Black



12" x 12"



18" x 18"



2" x 2" Mosaic



6" x 6"

Cotto Americana

PORCELAIN STONE

Sizes Available

Nominal (in)	Actual (in)	Thickness (in)	Finish
6 x 6†	5-13/16 x 5-13/16	3/8	UPS
12 x 12	11-13/16 x 11-13/16	3/8	UPS
18 x 18	17-13/16 x 17-13/16	3/8	UPS
2 x 2 Mosaics*	11-13/16 x 11-13/16	3/8	UPS

* 2 x 2 mosaic tile in 11-13/16 x 11-13/16 mounted sheets.

† The cut/bevel tile is cut from larger format tile and the edges are beveled to provide a factory appearance. Please allow two to eight weeks for delivery depending on Crossville's production schedule.

Coordinating Trim (available in all colors)

4 x 12 Single Bullnose	3-3/4 x 11-3/4	3/8	UPS
6 x 12 Cove Base	5-3/4 x 11-3/4	3/8	UPS



4" x 12" Bullnose



6" x 12" Cove Base

Shade & Texture Index

Cotto Americana has a shade variation of V4



V1



V2



V3



V4

V1=Uniform Appearance
V2=Slight Variation
V3=Moderate Variation
V4=Substantial Variation

Recommended Usage

Cotto Americana is recommended for interior floors, walls, countertops and exterior walls in both residential and commercial applications. If offset pattern is required on tiles 18 inches or longer, Crossville recommends an offset of not greater than 33%. See crossvilleinc.com for detailed installation instructions.

Wet Area Use For Mosaic Tiles

Crossville® 2" x 2", 3" x 3" and 2" x 4" mosaics exceed ADA guidelines and deliver a wet static coefficient of friction equal to or greater than 0.6 on the surface of the tile. Their small size ensures frequent grout joints which provides traction and drainage.

Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water, and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Crossville's mosaics to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Care and Maintenance

Regular cleaning is the best way to keep Cotto Americana tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville products is available at crossvilleinc.com.

Product Performance

Breaking Strength	>450 lbf.	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.10%	ASTM C373
Scratch Hardness	7	MOHs Scale
Coefficient of Friction		
Dry	>0.7	ASTM C1028
Wet	>0.6	ASTM C1028



Product featured in photo: AV172 Tan 6" x 6", 12" x 12"



Product featured in photo above: AV173 Red 12" x 12"