



Main Street

PORCELAIN STONE

- Contemporary color palette
- Neutral colors enhanced by subtle stone look
- Extremely durable for long-lasting beauty
- High COF and low maintenance ideal for commercial settings




AV211 Cinema Champagne




AV212 Café Caramel



AV213 Bistro Brown



AV214 Gallery Grey



AV215 Boutique Black

Sizes available (shown in Bistro Brown)



18" x 18"




6" x 18"



12" x 12"



6" x 6"



2" x 2" Mosaics
(Mesh mounted on
12" x 12" sheet.)



SCS CERTIFIED
RECYCLING
PROGRAM
SCIENTIFIC CERTIFICATION SYSTEMS
SERVICES

AV211 and AV212 have
4%, AV213, AV214, and
AV215 have 20%



Sizes Available

Nominal (in)	Actual (in)	Thickness (in)	Finish
2 x 2 Mosaics*	11-13/16 x 11-13/16	3/8	UPS
6 x 6	5-13/16 x 5-13/16	3/8	UPS
6 x 18	5-13/16 x 17-13/16	3/8	UPS
12 x 12	11-13/16 x 11-13/16	3/8	UPS
18 x 18	17-13/16 x 17-13/16	3/8	UPS

*Mesh mounted.

Coordinating Trim (available in all colors)

4 x 12 Single Bullnose	3-3/4 x 11-3/4	3/8	UPS
6 x 12 Cove Base	5-7/8 x 11-3/4	3/8	UPS



4" x 12" Bullnose



6" x 12" Cove Base

Product Performance

Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.10%	ASTM C373
Scratch Hardness	7	Mohs Scale

Static Coefficient of Friction

UPS	Dry	>0.85	ASTM C1028
	Wet	>0.7	ASTM C1028

Recommended Usage

Main Street is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Main Street is not recommended for exterior horizontal surfaces or exterior paving. If offset pattern is required on tiles 18 inches or longer, Crossville recommends an offset of not greater than 33%. See CrossvilleInc.com for detailed installation instructions.

Care and Maintenance

Regular cleaning is the best way to keep Main Street tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Recycling Process

Main Street contains between 4 and 20 percent pre-consumer recycled content and is manufactured by Crossville® using processes that have been certified by Scientific Certification Systems. SCS has verified that through these recycling processes Crossville recycles nearly 12 million pounds of previously discarded filtrate and fired tile waste. In addition to its own fired waste recycling, Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back™ Program. For more information, visit CrossvilleInc.com/green.

Shade & Texture Index

Main Street has a shade variation of V3.



V1



V2



V3



V4

V1=Uniform Appearance
V2=Slight Variation
V3=Moderate Variation
V4=Substantial Variation

This porcelain tile product is produced with a V3 variation. Expect that the amount of color and texture on each piece may vary significantly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

Wet area use for Main Street 2" x 2" mosaics

Crossville® produces these products with the Cross-Sheen® finish. They exceed current ADA guidelines and deliver a wet static coefficient of friction equal to or greater than 0.6 on the surface of the tile. Their small 2" x 2" size ensures frequent grout joints which provides traction and drainage.

Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Main Street to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.



Main Street
Floor: AV212 Café Caramel 18" x 18"

Crossville, Inc. • P.O. Box 1168, Crossville, TN 38557
Phone: 931.484.2110 • Fax: 931.456.2956
E-Mail: Crossc@CrossvilleInc.com • CrossvilleInc.com

 **CROSSVILLE**
ELEVATE YOUR SPACE