

# Strong

PORCELAIN STONE

- Shading variations within each color accentuate the look of natural slate
- All sizes are 3/8" thick for exceptional strength
- Ideal for high-traffic areas
- Five modular sizes offer unlimited design flexibility
- Easy to clean and maintain



VS100 Almond



VS101 Beige




VS102 Brown



VS103 Giallo



VS104 Verde



VS105 Nero

## Sizes Available

Size (in)	Actual (in)	Thickness (in)	Finish
6 x 6	5-3/4 x 5-3/4	3/8	UP
6 x 12	5-3/4 x 11-3/4	3/8	UP
12 x 12	11-3/4 x 11-3/4	3/8	UP
12 x 18	11-3/4 x 17-3/4	3/8	UP
18 x 18	17-3/4 x 17-3/4	3/8	UP

## Coordinating Trim available in all colors:

3 x 12 Bullnose	3-1/4 x 11-3/4	3/8	UP
-----------------	----------------	-----	----



3' x 12' Bullnose

## Recommended Usage


Strong Series is recommended for interior walls, floors and exterior walls in both residential and commercial applications. If offset pattern is required on tiles 18 inches or longer, Crossville recommends an offset of not greater than 33%. See [crossvilleinc.com](http://crossvilleinc.com) for detailed installation instructions.

## Care and Maintenance

Regular cleaning is the best way to keep your porcelain stone looking new for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville Porcelain Stone products is available at [CrossvilleInc.com](http://CrossvilleInc.com).

## Shade & Texture Index

Strong has a shade variation of V3



V1

V2

V3

V4

V1=Uniform Appearance  
V2=Slight Variation  
V3=Moderate Variation  
V4=Substantial Variation

## Product Performance

Frost Resistance	Resistant	ASTM C1026
Chemical Reaction	Unaffected	ASTM C650
Scratch Hardness	9	Mohs Scale
Bond Strength	>200 psi	ASTM C482
Breaking Strength	>475 lbs.	ASTM C648
Coefficient of Friction (Dry)	>0.8	ASTM C1028
Coefficient of Friction (Wet)	>0.6	ASTM C1028
Water Absorption	<0.20%	ASTM C373





Strong  
Giallo VS103 – 12"x 12", 18"x 18"  
Verde VS104 – 6"x 6", 12"x 12", 12"x 18", 18"x 18" and 3"x 12" bullnose  
Also featured is tile from Crossville's Stainless Steel Series:  
Brushed Finish, MT210 – 2"x 2", 6"x 6", 1"x 8" and 2"x 8" liner bars

Crossville, Inc. • P.O. Box 1168, Crossville, TN 38557  
Phone: 931.484.2110 • Fax: 931.456.2956  
E-Mail: [Crossc@CrossvilleInc.com](mailto:Crossc@CrossvilleInc.com) • [CrossvilleInc.com](http://CrossvilleInc.com)

 **CROSSVILLE**  
ELEVATE YOUR SPACE