

Tuscan Clay

PORCELAIN STONE

- Hand-crafted look and feel
- Appeal of terra cotta with the ease of maintenance and durability of Porcelain Stone®

- Multiple shapes and sizes including planks
- Four contemporary colors designed for blended installations




AV161 Bianco



AV162 Rosso



AV163 Marrone



AV164 Grigio

Sizes Available



16" x 16"



12" x 12"



8" x 8"



4" x 8"



4" x 4"



3" x 16"



3" x 3"



3" x 12"

Sizes Available

Nominal (in)	Actual (in)	Thickness (in)
3 x 3	2-13/16 x 2-13/16	3/8
3 x 1	2-13/16 x 11-13/16	3/8
3 x 16	2-13/16 x 15-13/16	3/8
4 x 4	3-13/16 x 3-13/16	3/8
4 x 8	3-13/16 x 7-13/16	3/8
8 x 8	7-13/16 x 7-13/16	3/8
12 x 12	11-13/16 x 11-13/16	3/8
16 x 16	15-13/16 x 15-13/16	3/8

Coordinating Trim Sizes (Available in all colors)

4 x 8 Single Bullnose	3-3/4 x 7-3/4	3/8
4 x 4 Bullnose Corner	3-3/4 x 3-3/4	3/8



4" x 4" Bullnose Corner



4" x 8" Single Bullnose

Shade & Texture Index

Tuscan Clay has a shade variation of V4



V1



V2



V3



V4

V1=Uniform Appearance
V2=Slight Variation
V3=Moderate Variation
V4=Substantial Variation

Installation Note

Installations pictured were created by blending tile from multiple cartons. Follow the installation instructions provided in product packaging and at crossvilleinc.com to achieve comparable results. If offset pattern is required on tiles 18 inches or longer, Crossville recommends an offset of not greater than 33%. See crossvilleinc.com for detailed installation instructions.

Recommended Usage

Tuscan Clay is recommended for interior floors, walls and countertops and exterior walls in both residential and commercial applications.

Care and Maintenance

Regular cleaning is the best way to keep Tuscan Clay tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. No waxes or sealers are needed. More information regarding the care and maintenance of Crossville products is available at crossvilleinc.com.

Product Performance

Breaking Strength	>450 lbf.	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.10%	ASTM C373
Scratch Hardness	7	MOHs Scale
Visible Abrasion		ASTM C1027
AV161	Class 4	
AV162	Class 2	
AV163, AV164	Class 3	
Coefficient of Friction		
Dry	>0.7	ASTM C1028
Wet	>0.6	ASTM C1028





Tuscan Clay
Floor: AV162 Rosso 3' x 3', 3' x 16" and 16' x 16"

Crossville, Inc. • P.O. Box 1168, Crossville, TN 38557
Phone: 931.484.2110 • Fax: 931.456.2956
E-Mail: crossc@crossvilleinc.com • crossvilleinc.com

 **CROSSVILLE**
ELEVATE YOUR SPACE