

*Main Street*



PORCELAIN STONE®

 CROSSVILLE®  
ELEVATE YOUR SPACE

# *Main Street*

*Contemporary color palette*

*Neutral colors enhanced by subtle stone look*

*Extremely durable for long-lasting beauty*

*High COF and low maintenance  
ideal for commercial settings*



Product featured in photo above: AV212 Café Caramel 18" x 18"



Products featured in photo above: AV211 Cinema Champagne 12" x 12"



Product featured in photo at right: AV215 Boutique Black 6" x 18"

Products featured on front cover: AV213 Bistro Brown 6" x 6", 12" x 12", 6" x 18"

## Colors



AV211 Cinema Champagne  
4% pre-consumer recycled content\*



AV212 Café Caramel  
4% pre-consumer recycled content\*



AV213 Bistro Brown  
20% pre-consumer recycled content\*



AV214 Gallery Grey  
20% pre-consumer recycled content\*



AV215 Boutique Black  
20% pre-consumer recycled content\*

\*Note: This product contains pre-consumer recycled content. Percentage varies by color.

This porcelain tile product is produced with a V3 variation. Expect that the amount of color and texture on each piece may vary significantly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

## Sizes (Available in all colors. Shown in AV215 Boutique Black)



18" x 18"



6" x 18"




12" x 12"



6" x 6"

## Mosaics



2" x 2" Mosaics  
(Mesh mounted)

### Wet area use for Main Street 2" x 2" mosaics

Crossville® produces these products with the Cross-Sheen® finish. They exceed current ADA guidelines and deliver a wet static coefficient of friction equal to or greater than 0.6 on the surface of the tile. Their small 2" x 2" size ensures frequent grout joints which provides traction and drainage.

Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water, and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Main Street to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.





# Main Street

## Sizes and Finishes

### Field Tile (Available in all colors)

Nominal (in)	Actual (in)	Thickness (in)	Finish
2 x 2 Mosaics*	11-13/16 x 11-13/16	3/8	UPS
6 x 6	5-13/16 x 5-13/16	3/8	UPS
6 x 18	5-13/16 x 17-13/16	3/8	UPS
12 x 12	11-13/16 x 11-13/16	3/8	UPS
18 x 18	17-13/16 x 17-13/16	3/8	UPS


\*Mesh mounted

### Coordinating Trim (Available in all colors)

Nominal (in)	Actual (in)	Thickness (in)	Finish
4 x 12 Single Bullnose	3-3/4 x 11-3/4	3/8	UPS
6 x 12 Cove Base	5-7/8 x 11-3/4	3/8	UPS



4 x 12 Bullnose



6 x 12 Cove Bullnose

## Product Performance

Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.10%	ASTM C373
Scratch Hardness	7	Mohs Scale

## Static Coefficient of Friction

UPS	Dry	>0.85	ASTM C1028
	Wet	>0.7	ASTM C1028

## Care and Maintenance

Regular cleaning is the best way to keep Main Street tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at [www.crossvilleinc.com](http://www.crossvilleinc.com).

## Recommended Use

Main Street is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Main Street is not recommended for exterior horizontal surfaces or exterior paving. If offset pattern is required for tiles longer than 18 inches, Crossville® recommends an offset of not greater than 33%. See [crossvilleinc.com](http://crossvilleinc.com) for detailed installation instructions.

## Shade & Texture Index

Main Street has a shade variation of V3.



V1



V2



V3



V4

V1=Uniform Appearance  
V2=Slight Variation  
V3=Moderate Variation  
V4=Substantial Variation

Product featured in photo above: AV214 Gallery Grey 6" x 18" and AV215 Boutique Black 2" x 2" Mosaics

## EcoCycle Recycling Processes™

Main Street contains between 4 and 20 percent pre-consumer recycled content and is manufactured by Crossville® using processes that have been certified by Scientific Certification Systems. SCS has verified that through these recycling processes Crossville recycles nearly 12 million pounds of previously discarded filtrate and fired tile waste. In addition to its own fired waste recycling, Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back™ Program. For more information, visit [www.crossvilleinc.com/green](http://www.crossvilleinc.com/green).



Crossville, Inc. • P.O. Box 1168, Crossville, TN 38557  
Phone: 931.484.2110 • Fax: 931.456.2956  
E-Mail: [crossc@crossvilleinc.com](mailto:crossc@crossvilleinc.com) • [www.crossvilleinc.com](http://www.crossvilleinc.com)

**CROSSVILLE**  
ELEVATE YOUR SPACE