



Colors



AP880 ▶ Onyx



AP001 ▶ Grey Mingle*

* Grey Mingle is made from a minimum of 30% recycled content, including up to 4% outside post-consumer waste.

- Suitable for floors that require extremely high breaking strength
- Vibration or traditional thinset installation
- Cross-Sheen® for added stain resistance
- Made in the U.S.A.

Recommended Use


Auto service bays and other areas where heavy weight and high vehicular traffic place greater stress loads on flooring systems. This hard, impervious porcelain tile is 15mm thick, to insure supportive strength and greater impact resistance. In addition the combination of impervious porcelain tile with the Cross-Sheen® finish provides a high degree of chemical resistance and insures ease of cleaning.

Care and Maintenance

Regular cleaning is the best way to keep AutoPaver™ tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Sizes (Available in all colors)



Sizes & Finishes

Field Tile - Rectified

Available in all colors

Nominal (in)	Actual (mm)	Thickness (mm)	Finish
3-3/4 x 8	97 x 200	15	UPS

Crossville recommends a grout joint of 3mm.

Actual measurements stated in inches indicate tile is calibrated (non-rectified).

Actual measurements stated in mm indicate tile is rectified.

Product Performance

Breaking Strength	1,000 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	6	Mohs Scale

Wet Dynamic Coefficient of Friction Range


Unpolished	≥0.42	AcuTest sm
------------	-------	-----------------------

German Ramp Value

Unpolished	R10	DIN 51130
------------	-----	-----------

Shade & Texture Index

AutoPaver has a shade variation of V1.



This porcelain tile product is produced with a V1 variation. Differences among pieces from the same production run are minimal.

Your Contacts

Samples / Order Fulfillment / Pricing -

Toni Hale / National Accounts Customer Service Manager
thale@crossvilleinc.com / (931) 484-2110 ext 3997

Website - www.crossvilleinc.com

Crossville Sample Express

Crossville, Inc. PO Box 1168
Crossville, TN 38557
E-Mail Crossc@CrossvilleInc.com
Web CrossvilleInc.com
Phone 931.484.2110
Fax 931.456.2956

Sample Fulfillment & Help
Samples@CrossvilleInc.com
1.800.221.9093

Trade Organizations



Environmentally Aware

